



To specify a wireless product variant for use with Philip Payne SpectoXT Emergency Lighting System from this range simply replace gear suffix code with XT.

### Specification

Supply Voltage	220-240V, 50-60Hz
IP	40
Weight	1.5kg
Beam Angle	29° or 63°
Luminous Flux 29°	258 Lumens
Luminous flux 63°	258 Lumens
Emergency Lighting Factor	100%
LED Watts	2 Watts
LED Drive Current	350mA

### PART NUMBERS

		29° VERSION
AVUN293LN	3hr	Non-Maintained
AVUN293LA	3hr	Mains/ Central Battery
AVUN293DS	3hr	Non-Maintained DALI

### PART NUMBERS

		63° VERSION
AVUN633LN	3hr	Non-Maintained
AVUN633LA	3hr	Mains/Central Battery
AVUN633DS	3hr	Non-Maintained DALI

### FINISH OPTIONS

<b>W</b> RAL 9010	<b>K</b> RAL 9005
<b>G</b> RAL 9006	<b>V</b> Penny Bronze

Products should be suffixed with the appropriate finish code.  
**AVUN293LNG** for grey finished product.

<b>SELF TEST</b>	<b>DALI</b>
EN60598-1	
EN60598-2-22	
EN55015	
EN61547	
EN61000-3-2	
STEEL/Aluminium	

