



SpectoXT

To specify a wireless product variant for use with Philip Payne SpectoXT Emergency Lighting System from this range simply replace gear suffix code with XT.

Specification

Supply Voltage	220-240v, 50-60Hz
IP	20
Weight	3.7kg
Beam Angle	29° or 63°
Luminous Flux 29°	2 x 325 Lumens
Luminous Flux 63°	2 x 345 Lumens
Emergency Lighting Factor	100%
LED Watts	2 x 3.5 Watts
LED Drive Current	300mA

PART NUMBERS

29° VERSION

AVTN296LN	3hr	Non-Maintained
AVTN296LA	3hr	Mains/Central Battery
AVTN296DS	3hr	Non-Maintained DALI

PART NUMBERS

63° VERSION

AVTN636LN	3hr	Non-Maintained
AVTN636LA	3hr	Mains/Central Battery
AVTN636DS	3hr	Non-Maintained DALI

FINISH OPTIONS

W RAL 9010	K RAL 9005
G RAL 9006	V Penny Bronze

Products should be suffixed with the appropriate finish code. For example; **AVTN296LNK** for **black** finished product.

CE	F
LED	NM
SELF TEST	DALI
20	3.7 KG
EN60598-1	
EN60598-2-22	
EN55015	
EN61547	
EN61000-3-2	
STEEL/Aluminium	

