














PHILIP PAYNE | LANTIS

	
	
	
	
	
	
EN60598-1	
EN60598-2-22	
EN55015	
EN61547	
EN61000-3-2	
Polycarbonate	



SpectoXT

To specify a wireless product variant for use with Philip Payne SpectoXT Emergency Lighting System from this range simply replace gear suffix code with XT.

Specification

Supply Voltage	230V
IP	65
Weight	1.5kg
Luminous Flux-110	545 Lumens
Luminous Flux-300	950 Lumens
Luminous Flux-350	1655 Lumens

PART NUMBERS












LANT110LM	3hr Self Contained	Maintained/ Non-Maintained
LANT110DL*	3hr Self Contained	Maintained DALi/ Non-Maintained
LANT300LN	3hr Self Contained	Non-Maintained
LANT300DS	3hr Self Contained	Non-Maintained DALi
LANT350LA	230v AC/DC	Central Supply
LANT350DA	230v AC/DC	Central Supply DALi

*Mains mode is not switchable via DALi command on self-contained luminaires. DALi is for controlled testing and monitoring only. Please contact technical for more information.

FINISH OPTIONS

As shown

LANTIS LANE 350 | PHILIP PAYNE

	
	
	
	
	
	
EN60598-1	
EN60598-2-22	
EN55015	
EN61547	
EN61000-3-2	
Polycarbonate	




To specify a wireless product variant for use with Philip Payne SpectoXT Emergency Lighting System from this range simply replace gear suffix code with XT.

Specification

Supply Voltage	230V
IP	65
Weight	1.5kg

PART NUMBERS

LANE350LA	230v AC/DC	Central Supply
LANE350DA	230v AC/DC	Central Supply DALI
LANE350LM	3hr Self Contained	Maintained/ Non-Maintained
LANE350YL	3hr Self Contained	Self Test
LANE350DL	3hr Self Contained	DALI

FINISH OPTIONS

As shown