






**SpectoXT**  
 To specify a wireless product variant for use with Philip Payne SpectoXT Emergency Lighting System from this range simply replace gear suffix code with XT.



Specification	
<b>Voltage</b>	<b>230v</b>
<b>IP</b>	<b>20</b>
<b>Weight</b>	<b>1.5kg</b>
<b>Gear Options</b>	<b>230v central Supply 3hr Non-Maintained 3hr Maintained 3hr Self Test 3hr DALi</b>



**SM** - Surface Mounted  
**FM** - Flush Mounted



	<b>SELF TEST</b>
	<b>DALI</b>

- EN60598-1
- EN60598-2-22
- EN55015
- EN61547
- EN61000-3-2
- PC ABS

Example Product code		22	2	ARCP	W	LM	G
Options	Choices						
Light Source Options	Standard Backlit	1					
	C/W Downlight Option	2					
Body Colour Options	RAL9010	W					
	RAL9006	G					
	RAL9005	K					
Gear Options	Central 230V Battery	LA					
	Self Contained 3hr Battery	LM					
	DALI	DL					
	Self Test	YL					
Frame Options	Satin Chrome	R					
	Brass	B					
	Polished Chrome	C					
	RAL9010	W					
	RAL9005	K					
	RAL9006	G					
	BMA	D					
Penny Bronze	V						