

SPRITE 860 | PHILIP PAYNE

| | | | | | |
|--|-------------|------------------|--|--------------|-------------|
| | | SELF TEST | | EN60598-1 | EN61547 |
| | DALI | NM | | EN60598-2-22 | EN61000-3-2 |
| | | | | EN55015 | STEEL |



| | | | Wall to Luminaire | Luminaire to Luminaire | Lumen Output | Wattage | Drive Current | Dimensions | Mains | DALI Mains | 3hr NM | 3hr NM Self Test | 3hr NM DALi |
|---------|---|--------|-----------------------|----------------------------|--------------|---------|---------------|------------|-----------|------------|-----------|------------------|-------------|
| SPRA860 | 2m wide escape route with 1 Lux on centreline | BS5266 | 5.2m | 12.3m | 200 | 2 Watts | 600mA | | SPRA860LA | SPRA860DA | SPRA860LN | SPRA860YS | SPRA860DS |
| | Open Area with 0.5 Lux minimum excluding 0.5m border | BS5266 | 4.8m | 10.6m | 200 | 2 Watts | 600mA | | | | | | |
| SPRC860 | 2m Wide escape route with 1 lux on centreline | BS5266 | 6.7m | 17.5m | 175 | 2 Watts | 600mA | | SPRC860LA | SPRC860DA | SPRC860LN | SPRC860YS | SPRC860DS |
| | Open Area with 0.5 Lux minimum excluding 0.5m border | BS5266 | N/A | N/A | 175 | 2 Watts | 600mA | | | | | | |
| SPRE860 | 2m Wide escape route with 1 lux on centreline | BS5266 | 3.7m | 8.5m | 190 | 2 Watts | 600mA | | SPRE860LA | SPRE860DA | SPRE860LN | SPRE860YS | SPRE860DS |
| | Open Area with 0.5 Lux minimum excluding 0.5m border. | BS5266 | 3.5m | 7.2m | 190 | 2 Watts | 600mA | | | | | | |