

PHILIP PAYNE | SPRITE 870



EN60598-1	EN61547
EN60598-2-22	EN61000-3-2
EN55015	PC ABS
STEEL	

			Wall to Luminaire	Luminaire to Luminaire	Lumen Output	Wattage	Drive Current	Dimensions	Mains	DALi Mains	3hr NM	3hr NM Self Test	3hr NM DALi
SPRT870	1.2m escape route with 10.8 Lux average and 1 Lux minimum	NFPA101	4.7m	9.8m	555	4 Watts	700mA		SPRT870LA	SPRT870DA	SPRT870LN	SPRT870YS	SPRT870DS
	Open Area with 10.8 Lux average and 1 Lux minimum	NFPA101	2.9m	7.2m	555	4 Watts	700mA		SPRT870LA	SPRT870DA	SPRT870LN	SPRT870YS	SPRT870DS
SPRP870	2m Wide escape route with 1 lux on centreline	BS5266	4.7m	10.4m	555	4 Watts	700mA		SPRP870LA	SPRP870DA	SPRP870LN	SPRP870YS	SPRP870DS
		NFPA101	4.2m	9.2m									
	Open Area with 0.5 Lux minimum excluding 0.5m border.	BS5266	5.2m	12.1m	555	4 Watts	700mA						
NFPA101		2.7m	6.7m										