

SPRITE TRACK 860 | PHILIP PAYNE

				EN60598-1	EN61547
				EN60598-2-22	EN61000-3-2
				EN55015	STEEL

FINISH OPTIONS

W RAL 9016 **K** RAL 9005 **G** RAL 9006

Products should be suffixed with the appropriate finish code.
For example; **SPT**E**860**X**T**K**** for **black** finished product.



	Lumen Output	Wattage	Drive Current	Dimensions	3hr NM	3hr NM DALI	3hr NM XT
SPT E 860	190	2 Watts	600mA		SPT E 860LN	SPT E 860DS	SPT E 860XT
SPT A 860	200	2 Watts	600mA		SPT A 860LN	SPT A 860DS	SPT A 860XT

SPT E 860	0.5 lux				1 lux			
	A	B	D	E	A	B	D	E
Mounting Height								
2.0m	3.8	7.6	7.6	3.8	4.2	9.4	9.4	4.2
2.5m	4.3	9.4	9.4	4.3	4.8	11.0	11.0	4.8
3.0m	4.9	10.6	10.6	4.9	5.3	12.3	12.3	5.3
3.5m	5.2	12.2	12.2	5.2	1.9	13.5	13.5	1.9
4.0m	5.6	13.4	13.4	5.6	0.7	10.6	10.6	0.7
4.5m	5.8	14.6	14.6	5.8	0	10.1	10.1	0

SPT A 860	0.5 lux				1 lux			
	A	B	D	E	A	B	D	E
Mounting Height								
2.0m	2.7	5	5	2.7	2.9	6.4	6.4	2.9
2.5m	3.1	6.2	6.2	3.1	3.3	7.5	7.5	3.3
3.0m	3.5	7	7	3.5	3.8	8.5	8.5	3.8
3.5m	3.8	8.2	8.2	3.8	4.1	9.5	9.5	4.1
4.0m	4.1	9	9	4.1	4.3	10.4	10.4	4.3
4.5m	4.4	9.8	9.8	4.4	4.4	11.2	11.2	4.4