

# PHILIP PAYNE | SPRITE TRACK 870

EN60598-1	EN61547	LED	NM	XT	15 KG
EN60598-2-22	EN61000-3-2				
EN55015	STEEL				

  

DALI	20	CE
------	----	----



### FINISH OPTIONS

- W** RAL 9016
- K** RAL 9005
- G** RAL 9006

Products should be suffixed with the appropriate finish code.  
For example; **SPTE870XTK** for **black** finished product.

	Lumen Output	Wattage	Drive Current	Dimensions	3hr NM	3hr NM DALI	3hr NM XT
SPTE870	555	4 Watts	700mA		SPTE870LN	SPTE870DS	SPTE870XT
SPTA870	545	4 Watts	700mA		SPTA870LN	SPTA870DS	SPTA870XT

SPTE870	0.5 lux				1 lux			
	A	B	D	E	A	B	D	E
Mounting Height								
2.0m	3.4	7	7	3.4	3.6	8	8	3.6
2.5m	3.9	8	8	3.9	4.3	9.7	9.7	4.3
3.0m	4.4	9.2	9.2	4.4	4.9	11	11	4.9
3.5m	4.8	10.6	10.6	4.8	5.3	12.2	12.2	5.3
4.0m	5.2	11.6	11.6	5.2	5.8	13.3	13.3	5.8
4.5m	5.6	12.6	12.6	5.6	6.1	14.4	14.4	6.1

SPTA870	0.5 lux				1 lux			
	A	B	D	E	A	B	D	E
Mounting Height								
2.0m	4.5	10.4	10.4	4.5	5	11.5	11.5	5
2.5m	5.1	12	12	5.1	5.7	13.1	13.1	5.7
3.0m	5.7	13.2	13.2	5.7	6.2	14.7	14.7	6.2
3.5m	6.2	14.4	14.4	6.2	6.7	16	16	6.7
4.0m	6.6	15.8	15.8	6.6	7	17.3	17.3	7
4.5m	6.9	17.2	17.2	6.9	7.2	18.2	18.2	7.2