

## TM65 Mid-Level Calculation

**IONWSLM**

ION WALL, SURFACE, MAINTAINED



### Product Information

Weight	1.429 kg
Service Life	10 Years
Location of Manufacture	Solihull

Life Cycle Stage	kg CO <sub>2</sub> e	Percentage of Total	Notes
A1: Material Extraction	16.981 kgCO <sub>2</sub> e	57.52%	TM65 Assumption
A2: Transport	0.566 kgCO <sub>2</sub> e	1.92%	TM65 Assumption
A3: Manufacturing	4.059 kgCO <sub>2</sub> e	13.75%	
A4: Transport to Site	0.057 kgCO <sub>2</sub> e	0.19%	TM65 Assumption
B3: Repair	5.801 kgCO <sub>2</sub> e	19.65%	One battery replacement accounted for over 10 year product life
C2: Transport	0.019 kgCO <sub>2</sub> e	0.06%	
C3: Waste Processing	2.030 kgCO <sub>2</sub> e	6.88%	
C4: Disposal	0.007 kgCO <sub>2</sub> e	0.02%	TM65 Assumption
<b>Total: A1-A4, B3, C2-C4</b>	<b>29.519 kgCO<sub>2</sub>e</b>		
<b>Including Buffer Factor</b>	<b>38.375 kgCO<sub>2</sub>e</b>		

### Total Embodied Carbon

(TM65 Mid-Level Calculation)

**38.375**

**kg CO<sub>2</sub>e**

Calculated using CIBSE DT65 Embodied Carbon Calculator (Beta V1.3)

For further information, please contact [sales@philippayne.co.uk](mailto:sales@philippayne.co.uk)