

## TM65 Mid-Level Calculation

**ARDCRLM**

ARDEN, CEILING, RECESSED, MAINTAINED



### Product Information

Weight	1.298 kg
Service Life	10 Years
Location of Manufacture	Solihull

Life Cycle Stage	kg CO <sub>2</sub> e	Percentage of Total	Notes
A1: Material Extraction	12.248 kgCO <sub>2</sub> e	50.97%	TM65 Assumption
A2: Transport	0.514 kgCO <sub>2</sub> e	2.14%	TM65 Assumption
A3: Manufacturing	3.688 kgCO <sub>2</sub> e	15.35%	
A4: Transport to Site	0.051 kgCO <sub>2</sub> e	0.21%	TM65 Assumption
B3: Repair	5.658 kgCO <sub>2</sub> e	23.55%	One battery replacement accounted for over 10 year product life
C2: Transport	0.017 kgCO <sub>2</sub> e	0.07%	
C3: Waste Processing	1.844 kgCO <sub>2</sub> e	7.68%	
C4: Disposal	0.006 kgCO <sub>2</sub> e	0.03%	TM65 Assumption
Total: A1-A4, B3, C2-C4	24.027 kgCO <sub>2</sub> e		
Including Buffer Factor	31.235 kgCO <sub>2</sub> e		

### Total Embodied Carbon

(TM65 Mid-Level Calculation)

**31.235**

**kg CO<sub>2</sub>e**

Calculated using CIBSE DT65 Embodied Carbon Calculator (Beta V1.3)

For further information, please contact [sales@philippayne.co.uk](mailto:sales@philippayne.co.uk)